













• Suitable to work in high congested areas like small shops, offices, kitchens, schools, hospitals, bars, gyms, restaurants • Adjustable flow (automatic start-stop with solenoid valve) of the detergent solution depending on type of surface • Brush with quick release • Removable recovery tank • Available in battery version (36B) with integrated battery charger with data memory and for any type of batteries • Battery included • Squeegee lifting lever • Compact reclining handle with control switches • Easy access and simple service of the components.

## **Standard equipment:**



• 5.511.1346 PPL brush Ø 360 mm - 15"



4.508.1040
Front squeegee blade
L.537 mm - Th. 2.5 mm
4.508.1041
Rear squeegee blade
L.590 mm - Th. 3 mm



• 0.108.0061 On-board Battery charger CBHD1 12V 6A only for model code: 8.518.0003



• 0.107.0050 Maintenance free battery 12V 55Ah BT DC 4.2 only for model code: 8.518.0003

• 0.108.0025 Power cable 1,5 mt. only for model code: 8.518.0003





Watch the video on youtube: www.youtube.com/lavorpro

	Quick 36E	Quick 36B	
code	8.518.0004	8.518.0003	
power supply	230 V - 50 Hz	12 V	
scrubbing / squeegee width	360 / 460 mm	360 / 460 mm	
max working capacity	1260 m²/h	1260 m²/h	
detergent tank capacity	11 l / 2.91 gal	11 l / 2.91 gal	
recovery tank capacity	12-13 l / 3.2 gal	12-13 l / 3.2 gal	
traction	mechanical	mechanical	
RPM / pressure on the brushes	130/18 kg /40 lbs	130/18 kg /40 lbs	
brush motor power	370 W	250 W	
detergent solution system	solenoid valve	solenoid valve	
depression / vacuum motor	850 mmH <sub>2</sub> O/400 W	$650 \text{ mmH}_2\text{O}/250 \text{ W}$	
dimensions / weight	120x43x97 cm / 38kg	120x43x97 cm / 38kg	





The unit can be supplied mains ( 15 m cable available ) or battery powered. Reclining handle: fit on any operator's height and allowing the perfect cleaning also on 90° corners. Shock-absorbing covers, simple cleaning of the recovery tank, non marking wheels.

Easy access to mechanical parts ( easy maintenance of each component), removable recovery tank without tools.





User friendly analogic control panel. Control lever for brush operation and detergent water outflow.

General ON/OFF switch, brush and vacuum motor switch, solenoid valve operation switch.

Parabolic squeegee, easy rubber blades replacement. The floating brush plate and squeegee grant the right cleaning pressure on any type of floor.



## **Optional accessories:**



• 0.107.0002 Tubular battery Pb-acid 12V 118Ah C5



• 0.107.0063 GEL Battery 12 MFP 105 12V 105Ah C5



- 4.508.1058 Polyurethane front blade L.537 TH. 2,5
- 4.508.1059 Polyurethane rear blade L.590 TH. 3



• 5.511.1413 Tynex brush Ø 360 mm-14" • 5.511.1411 PPL 0,03 brush Ø 360 mm-14" • 5.511.1412 PES brush Ø 360 mm-14"



• 5.511.1129 EWU pad driver Ø 360mm-14"



- 6.508.0143
- Abrasive pad Ø 381 mm-15" - beige
- 6.508.0144
- Abrasive pad Ø 381 mm-15"
- green
- 6.508.0141
- Abrasive pad Ø 381 mm-15"
- black



4.512.0068 Extension electric cord 15 m with Schuko plug